



Rubber Profile SAL SBR/EPDM

Group: 1294

Application

Sound absorption lining for steel straps and pipe clamps (also according to DIN 4109). Application up to +110°C.

Technical Data

Material:	SBR/EPDM, black
Hardness:	45+/-5° Shore
Temperature range:	-40°C up to +110°C
Breaking elongation:	min. 500 %
Tear strength:	400 N/cm ²
Fire resistance:	Material category B2 (DIN 4102), non-dripping
Sound absorption:	Up to 18 dB(A)
Fully resistant to:	Diluted acids, lyes, alkaline solutions, water, aqueous solutions up to 70°C; No absorption of moisture
Partially resistant to:	Grease, mineral oil, animal or vegetable fats, ester and ketones
Not resistant to:	Hot oils, fuels, aliphatic and aromatic hydrocarbons and chloric gas
Durability:	Weatherproof, ageing and ozone-resistant, DIN 53508 and 53509 tested

Type	Steel strap [mm]	H [mm]	Number of ribs	Weight [kg/m]	Quantity roll [m]	Part number
STD 1	25 x 3.0	4.5	4	0.19	30	146502
STD 2	30 x 3.0	4.0	4	0.20	30	146511
STD 3	40 x 4.0	6.0	5	0.31	30	146520
STD 4	50 x 5.0	7.0	5	0.39	30	146539
STD 5	70 x 6.0	7.0	7	0.52	30	146548