



## GrainDrain TwinTube - Doublewall Drainage

### Description:

GrainDrain TwinTube is produced in PE in the diameters (OD) Ø 90, 100, 110, 125, 160 and 200mm. The standard colors are blue and black, but production in other colors is possible. Every coil is equipped with a standard click-socket and can be wrapped with Nylon Stocking, Polyester Geotextile (Tygar), PP 450/700/1000\* fibres or Coco-fibres.

The innerwall of this double-wall pipe provides a steady waterflow.

\*PP1000 available up until Ø 100mm

OD	ID	Kn/m <sup>2</sup>	Perf/mm	Perf/m1	Rows
90	75	SN8	1,5x16	300	6
100	84	SN6	1,5x16	308	8
110	94	SN6	1,5x16	308	8
125	106	SN4	1,5x16	244	8
160	135	SN4	1,5x20	348	6
200	175	SN4	1,8x20	330	6
Slitted surface: > 50cm <sup>2</sup> per m1					

### Material:

Coils: 50 meter (Outer-wall PE-HD / Inner-wall PE-LD)  
 Lengths: 6 meter (Outer-wall PE-HD / Inner-wall PE-HD)  
 Per coil or length a click-socket is pre-mounted.

### Fittings:

Fittings are available for this item:

- T-Pieces\* (90° und 45°)
- Sockets
- Stops (PE-LD)

\* Not available in Ø 90 and 110mm.

### Application:

Suitable for applications with increased requirements such as:

- Deep-drainage
- Infiltration
- Vacuum extraction systems (unslotted)

The above mentioned data is based on our current knowledge and functions as non-binding information.

Due to the status of this item (in development) this information can change. Please check [www.grainplastics.nl](http://www.grainplastics.nl) for the most up to date information.

